

Lynx Plus Comparison to LynxR2

LYNXR2

Fixed English Display with no Backlight

30mA Piezo output + 120mA Bell Output

Internal Built-in Piezo Sounder and Speaker

2-Way Voice support over phone line only

40 Wireless zones, NO HARDWIRE ZONE

Compatible with 7845 ECP radios, GSML, and 7847i-L (not compatible with GSMLVP)

Uses GSM LED's for signal strength indicator

Uses External mounted GSM Antenna

When opened cover hangs on Ribbon cable

Dual PCB's

Internal sounder enabled/disabled via jumper

Larger Size 10.38"W x 7 1/8"H x 1 3/4"D

Has both an RJ11 and an RJ31X plug on board

Ships with X-10 Transformer

X-10 wires to screw terminals on board

LYNX PLUS

2-Line Backlit Alpha Display

120mA Bell Output Only (piezo output removed)

Internal Built- Speaker Only (Piezo removed)

2-Way Voice support over phone line and GSM

41 Zones (40 Wireless, 1 Hardwire)

Compatible with GSMVLP and 7847i-L only

Built in GSM Signal strength indicator

GSMVLP has built-in Antenna

Hinged Cover

Single PCB

Internal speaker enabled/disabled w/Dip switch

Smaller Size 8.8"W x 6.8"H x 1.9"D

RJ31X plug only on board

X-10 transformer and connector sold separately

X-10 Transformer plugs into PCB