

5800 Transmitters

Door/Window Transmitters

The 5800 Series of door and window wireless transmitters provide the most reliable, convenient and cost effective solutions for security protection. Powerful and versatile, these devices have been designed to solve the toughest, most labor-intensive installations—saving time and money.

With a demonstrated outdoor range of over a mile, the 5800 Series are the industry's best performing wireless transmitters.



FEATURES AND BENEFITS

5800MINI Door/Window Contact

Featuring an LED status indicator and a sleek, compact design, the 5800MINI is ideal for ornate doors, windows, casements and any application where aesthetics are critical. Available in both white and brown to match any décor.

5814 Ultra Small Door/Window Transmitter

The 5814 provides the perfect solution for difficult to reach places and applications where aesthetics and small size are important.

5815 Door/Window Transmitter

The 5815 is the ideal solution for installations where small size and aesthetics are important. It provides a reliable, convenient and cost-effective solution for door and window protection.

5815WG Door/Window Transmitter

When you need extra gap on an installation, select the 5815WG.

5816 Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches and wired closed circuit contact loop.

5800 Transmitters Technical Specifications

5800MINI DOOR/WINDOW CONTACT

- Signal transmission and low battery LED indicators
- Single-zone transmitter
- Sleek design virtually disappears
- Transmits supervisory, tamper and low battery
- Case tamper protection
- Magnet included
- Ideal for double-hung windows
- 3V lithium battery included
- Sensor dimensions: 1" W x 2.2" H x 0.25" D (25.4mm x 55.9mm x 6.4mm)
- Magnet dimensions: 0.25" x 0.25" x 1" (6.4mm x 6.4mm x 25.4mm)
- ETL Listed

5814 ULTRA SMALL DOOR/WINDOW TRANSMITTER

- Ideal for ornate doors/windows, casements, etc.
- Extremely compact
- Features a built-in reed switch and tamper
- Includes a supervised, replaceable CR2430 battery
- Dimensions: 1-1/2" H x 1-3/16" W x 5/8" D (38.1mm x 30.2mm x 15.9mm)

5815 DOOR/WINDOW TRANSMITTER

- New sleek design
- Two reed switches
- Transmits supervisory, tamper and low battery messages
- Includes a supervised replaceable CR123 battery
- Dimensions: 3" H x 1-1/2" W x 7/8" D (76.2mm x 38.1mm x 22.2mm)
- UL Listed

5815WG DOOR/WINDOW TRANSMITTER

- Sleek design
- Wide gap contact over 1.0"
- Single reed switch
- Aux terminals for wired devices
- Includes supervised, replaceable CR123 battery
- Dimensions: 3" H x 1-1/2" W x 7/8" D (76.2mm x 38.1mm x 22.2mm)
- UL Listed

5816 DOOR/WINDOW TRANSMITTER

- Includes a supervised replaceable CR123 battery
- Four pack of spare magnets (5899)
- Dimensions: 3-1/16" H x 1-9/16" W x 1-3/16" D (77.8mm x 39.7mm x 30.2mm)
- UL Listed

ORDERING

5800MINI	Door/Window Contact supplied with Lithium battery (White)
5800MINIBR	Wireless Door/Window Contact supplied with Lithium battery (Brown)
5814	Ultra Small Door/Window Transmitter
5815/5815WG	Door/Window Transmitter
5816	Door/Window Transmitter
5817XT	Three Zone Universal Transmitter
5817CBXT	Wireless Commercial Transmitter (UL Commercial Approved for Fire and Burglary)
5818MNL	Recessed Door Transmitter with Lithium battery supplied
5820L	Slimline Door/Window Contact Transmitter supplied with Lithium battery
5899	Four pack of spare magnets for 5816

Honeywell Security and Fire

2 Corporate Center Dr. Suite 100
P.O. Box 9040
Melville, NY 11747
1.800.323.4576
www.honeywell.com

L/5800TRAND/D | 04/17
© 2017 Honeywell International Inc.

Honeywell